

# CONVENTIONAL PNEUMATIC INDUSTRIAL TYRES

PNEUMATIC

SW

LT



**NM**  
non marking

- Deep tread.
- Good stability.
- Resistant to damage to sidewalls: Side wall structure.
- Good traction.
- Good driving comfort.
- Complete SET\*: Tyre + Tube + Flap.

#### APPLICATIONS

- Forklifts.
- Small - sized industrial tractors.
- Indoor trailers.
- Airport vehicles.

\*The conventional industrial tyres SW and LT are TT (Tube Type ) models for which complete assembly of tube and flap is recommended.



## CONVENTIONAL PNEUMATIC

### PNEUMATIC

CODE	TIRE SIZE	PROFILE	PR	TYPE	RIM WIDTH	INFLATION PRESSURE ETRTO (bar)	OVERALL DIAMETER (mm) ± 2%	OVERALL SECTION WIDTH (mm) ± 2%	LOAD CAPACITY (kg)		WEIGHT(kg)	
									8 km/h	16 km/h	Kg	Pound
4.00-8		WL	6	TT	3.00D-8	4.25	420	110	600	905	4.50	9.90
6.00-8		SW	8	TT	3.00D; 3.75L-8	8.25	485	160	950	1.435	8.10	17.82
16X4.5-8 (125/75-8)*		LT	12	TT	3.25L-8	10.00	385	122	750	1.130	4.20	9.24
16X6-8 (150/75-8)		SW	18	TT	4.33R-8	10.50	420	155	1.180	1.780	9.00	19.80
18X7-8 (180/70-8)		SW	16	TT	4.33R-8	10.00	465	175	1.650	2.490	12.30	27.06
6.00-9		SW	14	TT	4.00E-09	10.50	540	170	1.495	2.260	13.00	28.60
21X8-9(200/75-9)		SW	16	TT	6.00E-09	10.00	530	215	2.120	3.200	21.20	46.64
6.50-10		SW	14	TT	5.00; 5.50F-10	10.00	590	190	1.800	2.720	16.10	35.42
23X9-10 (225/75-10)		SW	20	TT	7.00F-10	10.00	585	230	2.650	4.000	23.30	51.26
7.00-10		SW	16	TT	5.00S-12	10.00	675	200	2.240	3.380	22.30	49.06
23X10-12 (250/60-12)		SW	22	TT	8.00G-12	10.50	600	260	2.985	4.510	30.30	66.66
27X10-12 (250/75-12)		SW	20	TT	8.00G-12	10.00	695	270	3.550	5.360	33.60	73.92
7.00-15		SW	16	TT	5.00; 5.50-15	10.00	740	205	2.725	4.115	24.60	53.90
7.50-15		SW	16	TT	5.00; 6.00; 6.50-15	10.00	785	225	3.000	4.530	27.70	60.94
28X9-15 (225/75-15)		SW	16	TT	7.0-15	10.50	715	220	3.090	4.665	27.10	59.62
32X12.1-15		SW	24	TT	9.75-15	10.30	810	325	4.835	7.300	64.70	142.34
8.25-15		SW	18	TT	6.0; 6.5; 7.0-15	9.25	840	255	3.650	5.510	43.20	95.04
250-15 (250/70-15)		SW	20	TT	7.0; 7.5-15	10.00	735	245	3.875	5.850	36.40	80.08
300-15 (315/70-15)		SW	20	TT	8.0-15	9.00	820	280	5.000	7.550	56.60	124.30
28X12 1/2-15 (355/45-15)		SW	24	TT	9.75-15	10.50	710	305	3730	5630	45.40	99.88
9.00-20		LT	14	TT	7.00-20	7.60	1.034	259	4.500	6.795	48.60	106.70
10.00-20		SW	20	TT	7.0; 7.50; 8.0-20	10.00	1.070	290	5.320	8.035	103.50	227.70
12.00-20		SW	20	TT	8.00; 8.50; 9.00-20	10.00	1.145	320	6.900	10.420	103.50	227.70